

# GLOBAL PAINT OIL FLOOR COLOR

HIGH QUALITY SYNTHETIC FLOOR COATING | WEATHER RESISTANT |  
EXCELLENT SCUFF- AND WEAR RESISTANCE

RESISTANT AGAINST HIGH PRESSURIZED CLEANSING | EXCELLENT BONDING |  
EASY SURFACE APPLICATION



<b>Use</b>	Indoor; Outdoor
<b>Gloss</b>	Satin-gloss
<b>Base</b>	White; Base P; Base TR
<b>Color</b>	Several selected colors
<b>Sizes</b>	1 Gallon
<b>Suitable</b>	Concrete; Metal; Asphalt; Floors; Walls; Wood; Et cetera

## PRODUCT INFORMATION

<b>Binder</b>	Urethane modified acrylic
<b>Density</b>	1.1 – 1.28 kg per liter (depending on the color)
<b>Solid Content</b>	62 – 65% depending on the color
<b>Spreading rate</b>	6 – 8 m <sup>2</sup> per liter at a wet layer thickness of 100 micron
<b>Shelf life</b>	12 months in unopened packaging; Keep cool and dry during storage

## APPLICATION DETAILS

<b>Application methods</b>	Brush; Roller; Spray
<b>Drying properties</b>	Dust dry after approximately 1 hour Tack free after approximately 8 hours Recoat able after approximately 24 hours
<b>Conditions during application</b>	Not to be applied in the full sun
<b>Thinner</b>	White spirit
<b>Cleaning equipment</b>	Clean immediately with White Spirit or thinner

## SYSTEMS

<b>Pre-treatment</b>	<ul style="list-style-type: none"> <li>Substrate has to be clean, dry and free from grease</li> <li>Eventually degrease with <b>GLOBAL PAINT ALL CLEAN</b></li> <li>Strong absorbing substrates must be treated with <b>GLOBAL PAINT OIL FLOOR PAINT</b> with diluted 10% white spirit</li> <li>After the pre-treatment finish with two full layers <b>GLOBAL PAINT OIL FLOOR PAINT</b> for the best result</li> </ul>
----------------------	--