

GLOBAL PAINT AQUATURA PRIMER

FAST DRYING | EXTREMELY GOOD SURFACE PENETRATION |
GOOD FILLING UNDERCOAT | SOLVENT-FREE

EASY TO APPLY | ESPECIALLY DEVELOPPED FOR SOLVENT-FREE PAINT SYSTEMS



Use	Indoor; Outdoor
Gloss	Flat
Base	White/Base P
Color	White
Sizes	¼ Gallon; 1 Gallon
Suitable	Doors; Panels; Wood; Frames; Fascia Boards; Groove Pine; T1-11; Et cetera

PRODUCT INFORMATION

Binder	Alkyd resin combination
Density	1.38 kg per liter
Solid content	56.5 %
Spreading rate	Approximately 8 – 10 m ² per liter depending on the surface of the substrate
Shelf life	12 months in unopened packaging; Keep cool and dry during storage

APPLICATION DETAILS

Application methods	Brush; Roller; Spray
Drying properties at 20°C	Dust dry after approximately 1 hour Tack-free after approximately 2 hours Recoat able after approximately 6 hours
Conditions during application	Stir well before use Optimal > 10°C and r.v. < 75%
Thinner	Water
Cleaning equipment	Clean with water after use

SYSTEMS

Pre-treatment	<ul style="list-style-type: none"> • Substrate has to be clean, dry and free from grease • Eventually degrease with GLOBAL PAINT ALL CLEAN • Smooth substrates have to be sanded • Before applying each new layer, flatten/sand surface well, preferably with an abrasive sponge • <i>Merbau</i>: When using this kind of wood, pre-treat it with an isolating base coat and finish with a dry film layer • <i>Iroko and Cedar</i>: When using this kind of wood, it's essential to degrease with thinner or boiling point benzine
----------------------	---