

GLOBAL PAINT AIR

100% ACRYLIC DISPERSION | LONG LASTING | ODORLESS WALL PAINT |
EASY TO CLEAN | EXCELLENT COVERAGE

HIGH QUALITY | LOW SOLVENT | EXCELLENT APPLICATION



Use	Indoor
Gloss	Flat
Base	White/Base P; D; ED; TR
Color	All Colors
Sizes	¼ Gallon; 1 Gallon; 5 Gallons
Suitable	Indoor walls; Plaster; Wallpaper; Drywall; Overcoat of paint; Concrete; Masonry

PRODUCT INFORMATION

Binder	100% acrylic dispersion
Density	1.48 kg per liter
Spreading rate	Approximately 8 – 10 m ² per liter depending on the porosity and surface of the substrate
Shelf life	12 months in unopened packaging; Keep cool and dry during storage

APPLICATION DETAILS

Application methods	Brush; Roller
Drying properties	Dust dry after approximately 1 hour Recoat able after approximately 12 hours
Conditions during application	Optimal between > 10 °C and r.v. < 75%
Thinner	Apply preferably in undiluted form. If necessary, with water.
Cleaning equipment	Clean tools immediately with warm water

SYSTEMS

Pre-treatment	<ul style="list-style-type: none"> Remove contaminants, powder and irregularities. Repair the substrate where necessary Carefully remove mold and soap residues with a suitable cleaning agent Remove any loose cement sludge skin from concrete The surface must be clean, dry and free of dust, if necessary, degrease with GLOBAL PAINT ALL CLEAN Highly absorbent, powdery surfaces and repairs must be fixed with GLOBAL PAINT AQUAFIX
Finish	<ul style="list-style-type: none"> Pre-treat untreated surfaces with GLOBAL PAINT WALLSEALER Depending on the substrate, finish with 1 or 2 layers of GLOBAL PAINT GLOBAL AIR