

KNV Roof Paint Roof Guard

Excellent and very good elastic and excellent weather proof roof paint acrylic based



- ✓ Provides a highly durable and weather-resistant finish
- ✓ Outstanding moisture resistance
- ✓ Durable elasticity and dirt repellent
- ✓ Hair cracks bridging
- ✓ The topcoat contains agents that inhibits growth of mildew on coating surface
- ✓ Excellent application properties / Low drip and run

Application:

Suitable for roof panels, ceilings, plaster, cement, brick walls, plasterboard etc. as well as over coats of dispersion paint with firm adhesion.

Product information	
Binder	Acrylic dispersion
Density	1.27 kg per liter
Spreading rate	8-10 m ² per ¼ gallon depending on surface texture & method of application
Gloss	Satin
Shelf life	<ul style="list-style-type: none"> • Shelf life 12 months in unopened packaging • Keep cool and dry during storage

Application details	
Application methods	Application with brush, lamb-wool roller or airless spraying gun, Spray pressure 80-100 bar nozzle 0.019-0.021 inch Stir thoroughly before use
Drying properties at 26°C	<ul style="list-style-type: none"> • Dust dry after app. 1 hour • Recoatable after app. 5 hours
Conditions during application	Not to be applied in the full sun
Thinner	0 – 5% water depending on surface texture & method of application
Cleaning equipment	Water

Supply	
Packing size	1 gallon and 5 gallons
Base	White/P, D, ED and TR
Color	All Colors

Systems

Pre-treatment

- Surface must be dry, with good adhesive properties, absorbent, neutral, clean, free of residue, dust, dirt and grease, cracks, mold and fungi.
- Fill gaps and cracks with filler. Fix constructional and structural cracks with a crack-bridging repair kit.
- Use **KNV ALL CLEAN ALL PURPOSE CLEANER** as cleaner/degreaser
- In case of strong absorbing or chalking substrates apply first **KNV AQUAFIX LIQUID BONDING PRIMER** and after drying apply 1 coat of **KNV Wallsealer** primer for optimal bonding strength.

Once the surface preparation has completed apply within 24 hours at least two full coats (or until a covered result is achieved), Allow adequate drying time between coats