

# KNV Wall Paint Colortex Interior

Elastic ceiling and wall paint based on pure acrylic dispersion for interior use



- ✓ Excellent application properties / low drip and run
- ✓ Washable and good moisture permeability
- ✓ Good opacity and extensibility
- ✓ Camouflages small cracks

## Application:

Suitable for plaster, cement, brick walls, drywall as well as over coats of dispersion paint with firm adhesion.

## Product information

<b>Binder</b>	Acrylic dispersion
<b>Density</b>	1.2 – 1.42 kg per liter
<b>Spreading rate</b>	App. 8 - 10 m <sup>2</sup> per ¼ gallon depending on the porosity and surface of the substrate
<b>Gloss</b>	Flat and Satin
<b>Shelf life</b>	<ul style="list-style-type: none"><li>• Shelf life 12 months in unopened packaging</li><li>• Keep cool and dry during storage</li></ul>

## Application details

<b>Application methods</b>	Application with brush, roller, spray or airless spraying gun
<b>Drying properties</b>	<ul style="list-style-type: none"><li>• Dust dry after app. 1 hour</li><li>• Recoatable after app. 8 hours</li></ul>
<b>Conditions during application</b>	Not to be applied in the full sun
<b>Thinner</b>	Water / Stir thoroughly before use

## Supply

<b>Packing size</b>	Quarter gallon, 1 gallon and 5 gallons
<b>Base</b>	White/Base P/D/ED/TR
<b>Color</b>	All colors

## Systems

### Pre-treatment

- Removable accurately disruptions and powdering paint layers  
WARNING: the old paint layers are crucial for the bonding and durable result.
- When applied on concrete remove the cement-hide slip first
- Fill gaps and cracks with filler. Fix constructional and structural cracks with a crack-bridging repair kit.
- Surface must be dry, with good adhesive properties, absorbent, neutral, clean, free of residue, dust, dirt and grease, cracks, mold and fungi.
- Greasy substrates must be preventive degreased by using **KNV ALL CLEAN ALL PURPOSE CLEANER**
- In case of a strong absorbing substrates apply first with **KNV WALLSEALER**