

KNV Wall Paint Weather Guard

Superior elastic ceiling and wall paint based on an acrylic dispersion for exterior or interior use



- ✓ Superior weather resistance and outdoor durability
- ✓ Excellent application properties / low drip and run
- ✓ Washable and good moisture permeability
- ✓ Good opacity and extensibility
- ✓ Camouflages small cracks

Application:

Suitable for plaster, cement, brick walls, drywall, as well as over coats of dispersion paint with firm adhesion.

Product information

Binder	Acrylic dispersion
Density	1.2 – 1.42 per liter
Spreading rate	App. 8 - 10 m ² per ¼ gallon depending on the porosity and surface of the substrate
Gloss	Flat, Eggshell, Satin and Semi-gloss
Shelf life	<ul style="list-style-type: none">• Shelf life 12 months in unopened packaging• Keep cool and dry during storage

Application details

Application methods	Application with brush, roller, spray or airless spraying gun
Drying properties	<ul style="list-style-type: none">• Dust dry after app. 1 hour• Recoatable after app. 8 hours
Conditions during application	Not to be applied in the full sun
Thinner	Water / Stir thoroughly before use

Supply

Packing size	Quarter gallon, 1 gallon and 5 gallons
Base	White/Base P/D/ED/TR
Color	All colors

Systems

Pre-treatment

- Removable accurately disruptions and powdering paint layers
WARNING: the old paint layers are crucial for the bonding and durable result.
- When applied on concrete remove the cement-hide slip first
- Fill gaps and cracks with filler. Fix constructional and structural cracks with a crack-bridging repair kit.
- Surface must be dry, with good adhesive properties, absorbent, neutral, clean, free of residue, dust, dirt and grease, cracks, mold and fungi.
- Greasy substrates must be preventive degreased by using **KNV ALL CLEAN ALL PURPOSE CLEANER**
- In case of a strong absorbing substrates apply first with **KNV WALLSEALER**