

KNV Wallsealer Extra Covering Power

Quick drying wallsealer based on acrylic dispersion for exterior and interior use.



- ✓ When applied in combination with **KNV Wall Paint** a powerful durable weather resistant substrate will be generated
- ✓ Penetrates deep into the substrate for optimal bonding strength
- ✓ Prevents peeling and blistering
- ✓ Excellent adhesive properties on powdering substrates
- ✓ Light pigmented
- ✓ Excellent application properties / Low drip and run
- ✓ Good hiding power
- ✓ Good moisture permeability
- ✓ Viscosity of a wall paint

Application:

Suitable for masonry and plasterwork, hardboard, concrete, and drywall

Product information	
Binder	Acrylic dispersion
Density	1.25 kg per liter
Spreading rate	8 – 10 m ² per ¼ gallon depending on the porosity and surface of the substrate
Gloss	Flat
Shelf life	<ul style="list-style-type: none"> • Shelf life 12 months in unopened packaging • Keep cool and dry during storage

Application details	
Application methods	To be applied either with a brush, roller or airless spraying gun
Drying properties	<ul style="list-style-type: none"> • Dust dry after app. 1 hour • Recoatable after app. 4 hours
Conditions during application	Not to be applied in the full sun
Thinner	0 - 5% water, depending on the porosity and surface of the substrate

Supply	
Packing size	Quarter gallon, 1 gallon and 5 gallons
Base	White/Base P
Color	White/Tintable

Systems

Pre-treatment

- Surface must be Clean and Dry, if necessary degrease with **KNV ALL CLEAN ALL PURPOSE CLEANER**
- Remove any salt corrosion on the masonry with a dry bristle