

KNV Whitex Wall & Ceiling Paint

Quick drying ceiling and wall paint based on copolymer dispersion for exterior and interior use



- ✓ Excellent weather resistance and outdoor durability
- ✓ Excellent application properties/ low drip and run
- ✓ Good opacity and extensibility
- ✓ Washable, good moisture permeability

Application:

Suitable for plaster, cement, brick walls, woodchip wallpaper, gyprock as well as over coats of dispersion paint with firm adhesion, Not suitable for textile or vinyl wallpaper.

Product information

Binder	Acrylic emulsion
Density	1.50 kg per liter
Spreading rate	10 – 12 m ² per ¼ gallon
Gloss	Flat
Shelf life	<ul style="list-style-type: none">• Shelf life 12 months in unopened packaging• Keep cool and dry during storage

Application details

Application methods	<ul style="list-style-type: none">• Application with brush, lamb wool roller or airless spraying gun• Stir thoroughly before use
Drying properties	<ul style="list-style-type: none">• Dust dry after app. 1 hour• Recoatable after app. 6 hours
Conditions during application	Not to be applied in the full sun
Thinner	If necessary, dilute with water

Supply

Packing size	Quarter gallon, 1 gallon and 5 gallons
Base	White
Color	White

Systems

Pre-treatment

- Surface must be dry, with good adhesive properties, absorbent, neutral, clean, free of residue, dust, dirt and grease, cracks, mold and fungi.
- Fill gaps and cracks with filler.
- Fix constructional and structural cracks with a crack-bridging repair kit.
- In case of strong absorbing substrates apply first **KNV WALLSEALER**