

KNV Wood & Metal Primer Oil Based

Quick drying thixotropic wood primer based on alkyd resin for exterior and interior use



- ✓ Excellent adhesion
- ✓ Excellent application properties
- ✓ Good extensibility
- ✓ Easy to sand
- ✓ Usable as a primer or as a intermediate coat in all alkyd paint systems

Application:

Specially formulated for excellent durability properties when used as a part of a conventional protective paint system on wood. Especially recommended for wood, hardboard, window and doorframes, etc. Primer to be top coated with alkyd or oil based finish coats.

Product information

Binder	Alkyd resin
Density	1.40 kg per liter
Spreading rate	8 – 10 m ² per ¼ gallon
Gloss	Flat
Shelf life	<ul style="list-style-type: none">• Shelf life 12 months in unopened packaging• Keep cool and dry during storage

Application details

Application methods	Application with brush, roller or spray gun
Drying properties	<ul style="list-style-type: none">• Dust dry after app. 1 hour• Tack free after app. 1 ½ hours• Recoatable after app. 4 hours
Conditions during application	Not to be applied in the full sun
Thinner	White Spirit

Supply

Packing size	Quarter gallon, 1 gallon, 2.5 gallons and 5 gallons
Base	White
Color	White & gray

Systems

KNV Wood & Metal Primer Oil Based • May 2020 • 1



Pre-treatment

- Surface must be abraded, clean and dry, with dust, dirt, wax and grease removed
- If excessive weathering has occurred exposing the original substrate the surface must be abraded
- The undercoat has to be sanded before applying the top coat
- Use **KNV ALL CLEAN ALL PURPOSE CLEANER** as a degreaser